

Optimizing Pallet Flow and Storage at General Mills

Del Williams

General Mills' Cedar Rapids, Iowa plant had successfully used pallet flow and pushback rack systems, but ongoing growth, product changes and long use required a storage system update that would safely add capacity to their existing facility.

General Mills values innovation in every aspect of its business, including storage and logistics. The plant's previous pallet flow and pushback rack systems had served almost 15 years. During that time, however, volumes had become larger, pallets heavier, and a switch from 50 lbs. bags of ingredients to 2,500 lbs. bulk super sacks was made, where possible, to enhance efficiency and minimize material handling, according to Scott Ladwig, an inventory analyst at the plant.

"The challenge was to make better use of our existing vertical warehouse space, since adding to our building was not an option," says Ladwig, who sought to avoid trailers of inventory sitting in the yard or contracted third-party storage. "We wanted to safely optimize our storage, inventory, and production." Ladwig turned to RMH Systems, a material handling equipment distributor, and Steel King, a flow storage system and pallet rack manufacturer. After consultation with General Mills and Steel King engineers, RMH Systems sales engineer Marty Frangenberg recommended and the plant implemented a new integrated SK 3400 flow storage and SK 3600 pushback rack system.

In a flow storage system, dynamic flow rails are inclined in a static rack structure, allowing loads placed on one end to move by gravity on rollers to the unloading end, with speed controllers acting as gentle brakes. As a load is removed, the loads behind it move forward automatically. Since the flow system depth, height, and width were limited only by the size of the facility and capabilities of the material handling equipment, it was a good fit for the plant's high volume, space efficient needs. Once loaded, FIFO product rotation is automatic and the rack eliminates labor and fork truck operation to arrange loads. Forklifts are required only for the initial and final unloading. Since only two aisles are necessary, aisle space could be reduced by 75 percent and up to 100 percent more product could be stored than with traditional selective pallet racking.

Optimizing Pallet Flow and Storage at General Mills

Published on Chem.Info (<http://www.chem.info>)



Pushback pallet rack systems offer up to 90 percent more product storage than selective rack systems and up to 400 percent more selectivity than drive-in racks. A dynamic pushback rack allows storing pallets two to five deep while providing easy access to a variety of different SKUs. Pallets are stored behind each other in a series of nested carts and are loaded from the same side of the system, eliminating separate aisles for each function. Composed of a stable rack along with a series of inclined carts and rails, when one pallet is pulled, the one behind it rolls forward.

“We consolidated the flow storage and pushback rack into an integrated system, and turned them both 90 degrees to free up floor space for corrugate storage,” explains Frangenberg. “This enhanced the flow of product and packaging materials to the production line, allowing high density storage and flow from end to end.” Ladwig adds, “Integrating the two separate racks into one rack system increased storage capacity by 42 percent and freed up space, allowing the addition of 24 percent more inventory items. It eliminated any issue of trailers of inventory sitting in the yard, and the potential need for contracted third-party storage space.”

To enhance rack longevity the General Mills plant chose SK3400 and SK3600 rack systems by Steel King both constructed with a bolted beam connection to structural channel columns. A number of rack features helped the company meet its strength, durability, and maintenance goals. Compared to typical racking, the pallet rack constructed of hot-rolled structural channel column with full horizontal-diagonal bracing offers greater frame strength, durability and cross-sectional area. All grade-5 hardware provides greater shear strength, and a heavy 7-gauge wrap-around connector plate ensures a square and plumb installation with a tighter connection and greater moment resistance. Special column punching in the structural rack provided two inches of adjustability to better accommodate the

Optimizing Pallet Flow and Storage at General Mills

Published on Chem.Info (<http://www.chem.info>)

dimensions of super sacks and larger pallet sizes. “We needed to adjust to larger pallet capacities now and into the future,” says Ladwig. “Simply raising or lowering our rack levels allows us to meet both current and future pallet sizes.”

To ensure rack safety and longevity, Frangenberg conducted a safety audit of the plant, and in collaboration with Ladwig as well as General Mills and Steel King engineers added a number of safety features to the rack and flow lanes. Along the plant’s previous pallet flow rack, fork truck operators had stacked product alongside the racking, causing some damage to the structure in the past. For added protection against such fork truck impact in the new system, pre-fabricated modular Steel Guard protective railing was installed. “The Steel Guard rails protect the sides of the rack from fork truck traffic, as well as give them a ‘backstop’ to place packaging up against one of their lay down areas,” says Frangenberg.

In the plant’s new pallet flow and pushback rack system, rack bays were widened to better accommodate new product weights and dimensions. According to Frangenberg, the wider rack bays also allowed for a larger “flue” along the upright runs for sprinkler dispersion, which helped to win approval of the design from General Mills’ insurance company. Pallet flow entry guides were installed to improve pallet flow in the flow lanes and allow more forgiving pallet placement. Along with this, heavy gauge pallet flow rollers were placed in the entry and exit flow lanes to better withstand pallet impact. Reinforced rail side channels were also used to hold the pallet flow rollers in place, and the rail channels were placed on thick structural angle for greater durability.

Perhaps most unique to the project, to prevent accidental overloading of the pallet flow rack, an anti-back up “pawl” system restricts any pallet from entry if the rack is already at capacity. “The ‘pawl’ system prevents pallets from being unintentionally pushed out the delivery side of the flow rack, and is designed with individual flippers that flip up to catch any size pallet,” says Ladwig.

“With our new integrated pallet flow and pushback rack system, our General Mills plant is operating more safely and efficiently than ever,” concludes Ladwig. “We’re ready for continued growth for the next 15 years and beyond.”

Source URL (retrieved on 02/01/2015 - 4:18am):

http://www.chem.info/articles/2013/10/optimizing-pallet-flow-and-storage-general-mills?qt-most_popular=1