

## Hydraulic Material Lift



Wildeck recently released the V-Lift™, a hydraulically operated, cantilever material lift. The lift can be installed in a shaftway or free-standing with optional structural framing. Features of the V-Lift™ include:

- ANSI/ASME B20.1 “Safety Standard for Conveyors” compliance.
- Guide columns constructed of 6-inch wide-flange structural steel.
- Hydraulic ram with large 2-1/2 inch diameter dual pistons for a smooth lifting motion.
- Single-cylinder hydraulic system that prevents twisting during operation.
- Standard carriage dimension of 6-ft × 6-ft with a lifting capacity up to 3,000 lbs.
- Safety interlocks, which prevent the VRC from moving unless the gates are fully closed.
- Optional carriages, ramps and controls.
- 100 percent phosphate-free paint pre-treatment process incorporating a non-toxic biodegradable alkaline powder that virtually eliminates the introduction of VOCs.

[info@wildeck.com](mailto:info@wildeck.com) [1]

[www.wildeck.com](http://www.wildeck.com) [2]

## Hydraulic Material Lift

Published on Chem.Info (<http://www.chem.info>)

---

**Source URL (retrieved on 01/26/2015 - 11:09pm):**

<http://www.chem.info/product-releases/2010/02/hydraulic-material-lift>

### Links:

[1] <mailto:info@wildeck.com>

[2] <http://www.wildeck.com>