

## A Diversity of Open-Channel Flow & Tank Levels



The Type 8136 non-contact radar level transmitter from Burkert is designed to measure open-channel flow and tank levels for a range of solids and liquids with dielectric values as low as 1.6. The 8136 unit also:

- Is available in 2 antenna versions—one with an encapsulated horn for aggressive liquids in small vessels, or another with a plastic horn for larger vessels or open flumes.
- Offers a measuring range of 0 to 65 feet.
- Implements a transmitter that is particularly suitable for continuous level measurement of toxic and corrosive substances, and ideal for flow measurement in open flumes used for wastewater treatment in chemical plants.
- Can be adjusted via a program module with an LCD display.

[marketing-usa@burkert.com](mailto:marketing-usa@burkert.com) [1]

[www.burkert-usa.com](http://www.burkert-usa.com) [2]

**Source URL (retrieved on 01/27/2015 - 11:14pm):**

[http://www.chem.info/product-releases/2010/03/diversity-open-channel-flow-tank-levels?qt-most\\_popular=1](http://www.chem.info/product-releases/2010/03/diversity-open-channel-flow-tank-levels?qt-most_popular=1)

## **A Diversity of Open-Channel Flow & Tank Levels**

Published on Chem.Info (<http://www.chem.info>)

---

### **Links:**

[1] <mailto:marketing-usa@burkert.com>

[2] <http://www.burkert-usa.com/>