

Wireless Audio Visual Alarm Stations



Detcon's new SW-AV1-DV1 and SW-AV1-DV2 wireless cordless audio visual alarm stations can operate continuously in full alarm condition for up to six hours using standard SmartWireless™ battery packs. The wireless alarm stations have two alarm levels with relay options that include adjustable set points and latching/non-latching relays: Alarm Level 1 activates the strobe and Alarm Level 2 initiates an audible warning device. Communication is performed using RXT-300 or RXT-320 SmartWireless™ transceivers. Alarm Level 2 can be configured for acknowledge/silence via operator interface at the SmartWireless™ HMI display panel when communicating by way of the RXT-320 transceiver. The RXT-300 transceiver has integrated processing capabilities and does not require a stand-alone controller to activate alarms. Alarm levels are set in the transceiver using a wireless configuration tool. Other features include:

- "Smart" battery packs that continuously report charge levels and estimated operating time before recharge or replacement is required.
- An optional solar charging panel that can be used to extend operating time and maintain a full battery charge in virtually any application.
- Class I Division 1 Groups C, D rating for the SW-AV1-DV1.
- Class I Division 2 Groups A, B, C, D rating for the SW-AV1-DV2.

sales@detcon.com
www.detcon.com [1]

Wireless Audio Visual Alarm Stations

Published on Chem.Info (<http://www.chem.info>)

Source URL (retrieved on *01/27/2015 - 8:17am*):

http://www.chem.info/product-releases/2011/01/wireless-audio-visual-alarm-stations?qt-recent_content=0

Links:

[1] <mailto:sales@detcon.com>