

Ideal for High Pressures & High Temperatures



Electro-Chemical Devices

introduces its CSX2 conductivity sensor for maximum reliability and an increased usable lifetime for harsh industrial processes in high-pressure, high-temperature environments. CSX2 features include:

- A 2-electrode sensor that measures electrolytic conductivity at a range of 1.0 to 50,000 μS .
- High-temperature service up to 200°C at pressures of 250 PSIG, in addition to low-temperature service below 100°C at pressures up to 400 PSIG.
- A 316 stainless steel outer body and center electrode, separated by a PEEK® internal insulator.
- EPR O-rings to double-seal all leak paths for maximum on-stream reliability.
- An explosion-proof, weather-resistant aluminum junction box that allows easy access to the terminal strip or the signal conditioner, which amplifies the conductivity signal, allowing noise-free transmission for hundreds of feet.
- Suitability for use in petrochemical refining, electric power generation, food/beverage, metals/mining or anywhere high-pressure steam boilers are in use.

sales@ecdi.com [1]

www.ecdi.com [2]

Ideal for High Pressures & High Temperatures

Published on Chem.Info (<http://www.chem.info>)

Source URL (retrieved on 01/30/2015 - 12:59pm):

http://www.chem.info/product-releases/2011/03/ideal-high-pressures-high-temperatures?qt-recent_content=0

Links:

[1] <mailto:sales@ecdi.com>

[2] <http://www.ecdi.com/>