

## Easy-Install Diaphragms



Wil-Flex's diaphragms are ideal for paint & coatings applications and, due to long flex life, have the ability to handle abrasion and a wide swing in pH levels. According to Wilden, the diaphragms' additional characteristics include:

- Flat profile design which eliminates the need to invert the diaphragm when rebuilding a pump.
- Made of Santoprene®, a thermoplastic elastomer that links EPDM (ethylene propylene diene Monomer) rubber and polypropylene, the diaphragms are an excellent low-cost alternative to PTFE diaphragms.
- Thermoplastic qualities give the diaphragms inherent tensile strength without fabric reinforcement.
- Currently available for use on the Advanced™ Series metal 25mm (1-inch) bolted stainless steel and aluminum, 38mm (1-1/2-inch) bolted stainless steel, and 76mm (3-inch) bolted stainless steel and aluminum models.
- Wilden's advanced bolted pumps also include the Pro-Flo X™ air distribution system that allows the pump user to control the flow rate and maximize efficiency to reduce processing costs.

[www.wildenpump.com](http://www.wildenpump.com) [1]

## Easy-Install Diaphragms

Published on Chem.Info (<http://www.chem.info>)

---

<http://www.chem.info/product-releases/2011/05/easy-install-diaphragms>

### Links:

[1] <http://www.wildenpump.com/>