

## Lift Loads up to 50 Pounds



TKF recently unveiled its Valu-Lift™ vertical lift as a light-duty, 4-strand, continuous-lift conveyor that can handle cartons and other smooth-bottom loads up to 50 pounds. Moreover, the Valu-Lift delivers:

- A maximum unit load of 21 inches (L) by 16 inches (W) by 22 feet (H).
- A minimum unit load without special transitions of 10 (L) by 4 (W) by 1-1/2 inches (H) with a weight of 3 pounds.
- Standard net lifting heights from 8 to 14 feet with customized heights available.
- The capacity to lift at a maximum speed of 118 FPM.
- Up, down or reversible operational modes.
- A patented platform consisting of lightweight interlocking molded polymer flights with steel connecting pins.
- Efficient, high-speed operation, low maintenance, and quick and easy assembly.
- Economical modular construction.
- Standard safety features that include a 24-VDC control, a current sensing relay that instantly shuts down the conveyor if it is overloaded, totally enclosed shroud-type tunnel guards and a smooth, clean design.

## Lift Loads up to 50 Pounds

Published on Chem.Info (<http://www.chem.info>)

---

[www.tkf.com](http://www.tkf.com) [2]

### Source URL (retrieved on *02/01/2015 - 8:43am*):

[http://www.chem.info/product-releases/2011/08/lift-loads-50-pounds?qt-most\\_popular=1](http://www.chem.info/product-releases/2011/08/lift-loads-50-pounds?qt-most_popular=1)

### Links:

[1] <mailto:sales@tkf.com>

[2] <http://www.tkf.com>