Eliminate False Reflections from Disturbances & Buildup

KROHNE recently launched its OPTIFLEX 2200 C/F level meter with software-based dynamic parasite rejection technology to eliminate false reflections caused by environmental disturbances and product buildup. The company further believes that this meter, which accommodates both liquids and solids, features:

- The measurement of level independent from such physical property variations as dielectric constants, pressure or density.
- A variety of probes to measure liquids up to 137 feet (40 m) and solids up to 66 feet (20 m).
- The capability to handle process temperatures up to 570°F (300°C) and pressures up to 580 PSIG (40 BAR).
- A remote converter that can be installed up to 328 feet (100 m) from the probe.
- A snap coupling system that permits removal of the housing under process conditions.
- A 2-wire design that incorporates time domain reflectometry guided radar technology.
- The ability to replace traditional level meters that require more maintenance, including displacer, radio frequency capacitance, conductive and pressure level meters.

- Suitability for tank and silo applications in the chemical industry, as well as in the oil and gas, energy, wastewater, mining, or pulp and paper sectors.
- Compliance with safety integrity level SIL 2.
- The flexibility to be used for switch or transmitter functionality in safety-related systems.

WEFTEC Booth #6413
info@krohne.com
[1]

www.us.krohne.com [2]

Source URL (retrieved on *03/07/2014 - 8:16pm*):
http://www.chem.info/product-releases/2012/07/eliminate-false-reflections-disturbances-buildup

Links:
[1] mailto:info@krohne.com
[2] http://www.us.krohne.com/